

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

---

1-20. (Cancelled.)

21. (Currently Amended) A communications method for an endpoint being one of (i) an Internet Protocol (IP) telephone and (ii) a telephone coupled to a terminal gateway, the communications method comprising:

registering a first line of the endpoint with a first communications server, and registering a second line of the endpoint with a second communications server, each of the first and second communications servers registers the endpoint by storing a telephone number, a logical line number, an Internet Protocol address and a Media Access Control (MAC) address of the endpoint;

establishing a first telephone call on the first line of the endpoint to a second endpoint via the first communications server; and

establishing a second telephone call on the second line of the endpoint to a third endpoint via the second communications server.

22. (Original) The communications method of claim 21 wherein establishing the second telephone call comprises establishing the second telephone call on the second line of the endpoint to a third endpoint via the second communications server, without disconnecting the first telephone call on the first line of the endpoint to the second endpoint via the first communications server.

23. (Original) The communications method of claim 21 further comprising receiving a third telephone call on the first line of the endpoint from a fourth endpoint via a third communications server.

24. (Original) The communications method of claim 21 wherein establishing the first telephone call comprises:

sending an off-hook message to the first communications server in response to detecting the first line going off hook;

receiving a dialtone message from the first communications server in response to sending the off-hook message;

sending the telephone number of the second endpoint to the first communications server;

receiving a ring message from the first communications server to the second endpoint;

receiving a connect message from the first communications server; and

communicating with the second endpoint in response to receiving the connect message.

25. (Previously Presented) A terminal gateway adapted to convert Internet Protocol (IP) media packets from a network into analog signals and to forward the analog signals to at least one endpoint via a dedicated communication link between the terminal gateway and the at least one endpoint, said terminal gateway comprising:

a memory including one or more instructions; and

a processor coupled to the memory, said processor, in response to the one or more instructions, to,

establish a first communication path between a first logical line of a first endpoint and a second endpoint via a first communication server coupled to the network, in response to a first input, and

establish a second communication path between a second logical line of the first endpoint and a third endpoint via a second communication server coupled to the network, in response to a second input, said second communication path being established via the second communication server independently of the first communication path.

26. (Original) The terminal gateway of claim 25 wherein the terminal gateway comprises at least part of the first endpoint.

27. (Original) The terminal gateway of claim 25 wherein the second and third endpoints are the same endpoint.

28. (Cancelled.)

29. (Cancelled.)

30. (Cancelled.)

31. (Cancelled.)

32. (Cancelled.)

33. (Previously Presented) An endpoint, being one of (i) an Internet Protocol (IP) telephone and (ii) a telephone coupled to a terminal gateway, for coupling to one or more communications servers, the endpoint comprising:

a first logical line for registering with a first communications server, said first logical line capable of receiving communications services from the first communications server; and

a second logical line for registering with a second communications server, said second logical line capable of receiving communications services from the second communications server.

34. (Original) The endpoint of claim 33 wherein the first and second logical lines are mapped to first and second keys on the endpoint.

35. (Original) The endpoint of claim 33 further comprising a terminal gateway for coupling to the first and second communications servers via a network, said terminal gateway converting signals representing communications calls on the first and second logical lines to packets on the network, and vice versa.

36. (Cancelled.)

37. (Cancelled.)

38. (Cancelled.)

39. (Currently Amended) An endpoint being one of (i) an Internet Protocol (IP) telephone and (ii) a telephone coupled to a terminal gateway, the endpoint comprising:  
means for registering a first line with a first ~~communications-telephony~~ server means via a network means;  
means for registering a second line with a second ~~communications-telephony~~ server means via the network means; and  
means for establishing a first communications call on the first line via the first ~~communications-telephony~~ server means, the first telephony server collaborates with the second telephony server if the first telephony server does not support a requested feature.; and  
~~means for establishing a second communications call on the second line via the second communication server means.~~

40. (Currently Amended) The endpoint of claim 39 further comprising wherein said means for establishing the second communications call ~~comprises means for establishing the second communications call on the~~ a second line via the second telephony communications server means, without disconnecting the first communications call on the first line via the first telephony communications server.

41. (Currently Amended) The endpoint of claim ~~39~~ 40 wherein said means for establishing the first communications call comprises:  
means for sending an off-hook message to the first communications server in response to detecting the first line going off hook;  
means for receiving a dialtone message from the first communications server in response to means for sending the off-hook message;  
means for sending a telephone number of a remote endpoint to the first communications server;  
means for receiving a connect message from the first communications server; and  
means for communicating with the remote endpoint in response to said means for receiving said connect message.

42. (Cancelled.)

43. (Cancelled.)

44. (Cancelled.)

45. (Cancelled.)

46. (Cancelled.)

47. (Cancelled.)

48. (Previously Presented) A terminal gateway adapted to convert Internet Protocol (IP) media packets from one or more communications servers into analog signals and to forward the analog signals to an endpoint via a dedicated communication link between the terminal gateway and the at least one endpoint, the terminal gateway comprising:

means for transmitting a first registration message to a first communications server for registering a first line of the endpoint;

means for updating a registration table registering the first line with the first communications server, responsive to receiving a first acknowledgement message from the first communications server;

means for transmitting a second registration message to a second communications server for registering a second line of the endpoint; and

means for updating the registration table registering the second line with the second communications server, responsive to receiving a second acknowledgement message from the second communications server.

49. (Original) The terminal gateway of claim 48 further comprising:

means for requesting a first call on the first line from the first communications server;

means for receiving a first connect message with an IP address of a first terminal gateway from the first communications server; and

means for communicating with the first terminal gateway using the IP address of the first terminal gateway.

50. (Original) The terminal gateway of claim 49 further comprising:  
means for requesting a second call on the second line from the second communications server;  
means for receiving a second connect message with an IP address of a second terminal gateway from the second communications server; and  
means for communicating with the second terminal gateway using the IP address of the second terminal gateway.

*B1  
concl.* 51. (Previously Presented) The communications method of claim 21, wherein the endpoint is a telephone.

52. (Previously Presented) The communications method of claim 21, wherein the endpoint, the second endpoint and the third endpoint are telephones that are collectively in communications with the first communications server and the second communications server.

---